



**F2 Labs**  
16740 Peters Road  
Middlefield, Ohio 44062  
United States of America  
[www.f2labs.com](http://www.f2labs.com)

## INDUSTRY CANADA TEST REPORT

---

**Manufacturer:** Quest Technologies, Inc.  
55 Chastain Road Northwest, Suite 100  
Kennesaw, Georgia 30144 USA

**Applicant:** SIP Technologies, LLC  
72070 Highway 1077  
Covington, Louisiana 70433 USA

**Product Description:** The Neo3 system consists of 2 boards housed in separate enclosures - Controller Board, High Voltage O3 Generator Board.

The Controller board includes a microcontroller, LCD display, keypad, Low voltage power supply, relay for controlling power to a water cooler and power switches for controlling power to the air pump and O3 generator circuit located in the High Voltage O3 Generator board.

The High Voltage Generator board consists of an air pump and a 10 KV pulse generator circuit. Using the keypad on the controller board, a user can program the times and the intervals for ozone generation. At the programmed times, the microcontroller applies power signals to the air pump and the ozone generator via a 3- conductor cable. The power signals turn on the high voltage and the air pump on the High Voltage O3 Generator board.

The high voltage creates a corona across a glass tube through which air is pumped. In the first step, the oxygen molecules in the glass tube are broken into 2 atoms (2 O) by the corona. In the second step, each of these highly reactive atoms combines with an oxygen molecule to produce an ozone molecule (O3). The Ozone thus produced is dissolved in water inside a cooler using a diffuser.

During normal operation, the SIP/Neo3 ozonator turns on at a user programmed time and runs for a certain duration entered by a user using the 3 keys on the front panel. Please see the User's manual for details on programming. The Ozone generated is pumped into a water cooler.

The main controller board is equipped with a 10 A fuse on the 110/220 VAC supply voltage.

**Operating Voltage/Frequency:** 230V/50 Hz

**Equipment Under Test:** SIP NEO3<sup>1</sup>  
Model: SIP NEO3\*

*\*Denotes actual model tested as worst-case representative of product family that includes the following: SIP-OS-1001, SIP-OS-1002, SIP-OS-1003, SIP NEO3.*

<sup>1</sup>SIP is a trademark of SIP Technologies, LLC.

**Equipment Category:** Information Technology Equipment

**Measurement Location:** F2 Labs in Middlefield, Ohio. Site description and attenuation data are on file with the Certification and Engineering Bureau, Industry Canada, Site Number 4730B-1.

**Measurement Procedure:** All measurements were performed according to Industry Canada outlined in Interference-Causing Equipment Standard for Digital Apparatus, ICES-003, Issue 6:2016 for Information Technology Equipment. A list of the measurement equipment is included with the test data.

**Canadian Standards Association Standard CAN/CSA-CISPR 22-10**, *Information technology equipment — Radio disturbance characteristics — Limits and methods of measurement*

**ANSI C63.4**, *American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz<sup>2</sup>* (latest published edition)

**Applicable Rules:** ICES-003, Issue 6:2016 for Class A IT Equipment\*

*\*Test results do not include radiated emissions, at request of client.*

**Product Received:** December 19, 2017

**Testing Completed:** March 22, 2018

**Summary of Results:** **In Compliance (with design changes noted in Exhibit II of this Test Report)\***

*\*Test results do not include radiated emissions, at request of client.*

The EUT complies with the EMC requirements when manufactured identically as the unit tested in this report, including any required modifications and/or Manufacturer's Statement. Any changes to the design or build of this unit subsequent to this testing may deem it non-compliant.



**Evaluation Conducted by:** Michael Toth, EMC Lab Manager



**Reviewed by:** Ken Littell, Director of EMC & Wireless Operations

Note: Complies/Does Not Comply criteria are based upon the following condition: Where the results are compared to published test standard or manufacturer specified limits, the Complies or Does Not Comply opinion is considered without applying the stated measurement of uncertainty.

This report shall not be duplicated except in full without the written approval of F2 Labs.  
Reports noted as a revision replace all previously issued reports and/or antecedent report revisions issued under this job number.

### Table of Contents

I.	Test Procedure and Data Calculation	4
II.	EUT Configuration and Cables	6
III.	Conducted Emissions	8
IV.	Photographs	13
V.	Modifications	14
VI.	Labeling	15

### Document History

Document Number	Description	Issue Date	Approved By
F2LQ9812A-05E	First Issue	April 25, 2018	K. Littell
F2LQ9812A-05E Rev. 1	Revision of manufacturer's name, addition of trademark information at client request.	May 15, 2018	K. Littell

## Exhibit I

### Test Procedure and Data Calculation

**Test Item Condition:**

The equipment to be tested was received in good condition.

**Testing Algorithm:**

EUT was set up in a normal operating mode, with device powered on and supplying power to a water cooler. The highest emissions were recorded in the data tables.

**Conducted Emissions:**

The equipment was installed on a non-conductive surface 10 cm above a GRP. Power was provided to the EUT through a LISN bonded to a 3 x 2 meter ground plane. The LISN and peripherals were supplied power through a filtered AC power source. The output of the LISN was connected to the input of the receiver via a transient limiter, and emissions in the range 150 kHz to 30 MHz were measured. The measurements were recorded using the quasi-peak and average detectors as directed by the standard, and the resolution bandwidth during testing was 9 kHz. The raw measurements were corrected to allow for attenuation from the LISN, transient limiter and cables. All data for conducted emissions can be found in Exhibit III.

**Uncertainty Budget:**

The uncertainty in EMC measurements arises from several factors which affect the results, some associated with environmental conditions in the measurement room, the test equipment being used, and the measurement techniques adopted.

The measurement uncertainty budgets detailed below are calculated from the test and calibration data and are expressed with a 95% confidence factor using a coverage factor of  $k=2$ . The Uncertainty for a laboratory are referred to as  $U_{lab}$ . For Radiated and Conducted Emissions, the Expanded Uncertainty is compared to the  $U_{cispr}$  values to determine if a specific margin is required to deem compliance.

$U_{lab}$

Measurement Range	Combined Uncertainty	Expanded Uncertainty
Radiated Emissions <1 GHz @ 3m	2.54	5.07dB
Radiated Emissions <1 GHz @ 10m	2.55	5.09dB
Radiated Emissions 1 GHz to 2.7 GHz	1.81	3.62dB
Radiated Emissions 2.7 GHz to 18 GHz	1.55	3.10dB
AC Power Line Conducted Emissions, 150kHz to 30 MHz	1.38	2.76dB
AC Power Line Conducted Emissions, 9kHz to 150kHz	1.66	3.32dB

$U_{cispr}$

Measurement Range	Expanded Uncertainty
Radiated Emissions <1 GHz @ 3m	5.2dB
Radiated Emissions <1 GHz @ 10m	5.2dB
Radiated Emissions 1 GHz to 2.7 GHz	Under Consideration
Radiated Emissions 2.7 GHz to 18 GHz	Under Consideration
AC Power Line Conducted Emissions, 150kHz to 30 MHz	3.6dB
AC Power Line Conducted Emissions, 9kHz to 150kHz	4.0dB

If  $U_{lab}$  is less than or equal to  $U_{cispr}$ , then:

- compliance is deemed to occur if no measured disturbance exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  in table 1, then:

- compliance is deemed to occur if no measured disturbance, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Note: Only measurements listed in the tables above that relate to tests included in this Test Report are applicable.

## Exhibit II

### EUT Configuration and Cables

**Equipment Under Test (EUT):**

Product Description: See page 1.


Device	Manufacturer	Model Number	Serial Number
SIP NEO3 <sup>1</sup>	QUEST Technologies, LLC	SIP NEO3*	None Specified

<sup>1</sup>SIP is a trademark of SIP Technologies, LLC.

*\*Denotes actual model tested as worst-case representative of product family that includes the following: SIP-OS-1001, SIP-OS-1002, SIP-OS-1003, SIP NEO3.*

Note: The EUT tested included the following design changes made to the EUT by the manufacturer, necessary to meet Conducted Emissions requirements:

- Replaced Qualtekk 703W-00/54 connector with YA10P-B IEC filtered connector.
- Replaced HLK-5M12 power supply module with filtered Zettler ZP05S1200WB module.
- Removed common mode choke and 2200pf capacitors and added 0.1uf film capacitor.



The EUT complies with the EMC requirements when manufactured identically as the unit tested in this report, including any required modifications and/or manufacturer's statement. Any changes to the design or build of this unit subsequent to this testing may deem it non-compliant.

**Accessories (Support Equipment):**

Device	Manufacturer	Model Number	Serial Number
Water Cooler	Quest Technologies, Inc.	Turbo Water Cooler	None Specified

**Cables:**

Cable Function	Length	Shielded (Yes/No)
AC Mains Input	>3m	No
AC Mains Output	<3m	No
DC Output	<3m	No




### Exhibit III

### Conducted Data

<b>Test Date:</b>	March 22, 2018	<b>Test Engineer:</b>	M. Toth
<b>Rule:</b>	ICES-003 Issue 6	<b>Air Temperature:</b>	21.0° C
<b>Limit:</b>	Class B	<b>Relative Humidity:</b>	35%
<b>Test Results:</b>	Complies*		


\*Complies with design changes noted in Section 4.1 of this Test Report.

### AC Mains Input, Conducted Test – Line 1: 0.15 MHz to 30.0 MHz




Top Discrete Measurements								
No.	Conductor	Frequency (MHz)	Detector	Level (dBµV)	Adjustment (dB)	Results (dBµV)	Limit (dBµV)	Margin (dB)
1	Line 1	0.44	Quasi-Peak	24.296	10.448	34.744	57.062	-22.318
		0.44	Average	18.810	10.448	29.258	47.380	-18.122
2	Line 1	0.44025	Quasi-Peak	24.874	10.448	35.322	57.057	-21.735
		0.44025	Average	19.895	10.448	30.343	47.374	-17.031
3	Line 1	0.463875	Quasi-Peak	26.580	10.430	37.010	56.623	-19.613
		0.463875	Average	21.745	10.430	32.175	46.811	-14.636
4	Line 1	0.7305	Quasi-Peak	25.486	10.336	35.822	56.0	-20.178
		0.7305	Average	19.496	10.336	29.832	46.0	-16.168
5	Line 1	0.733875	Quasi-Peak	24.526	10.336	34.862	56.0	-21.14
		0.733875	Average	19.923	10.336	30.259	46.0	-15.741
6	Line 1	3.55875	Quasi-Peak	20.772	10.308	31.080	56.0	-24.920
		3.55875	Average	12.986	10.308	23.294	46.0	-22.706
7	Line 1	3.7275	Quasi-Peak	21.577	10.311	31.888	56.0	-24.112
		3.7275	Average	14.593	10.311	24.904	46.0	-21.096
8	Line 1	3.76125	Quasi-Peak	21.922	10.309	32.231	56.0	-23.769
		3.76125	Average	14.484	10.309	24.793	46.0	-21.207
9	Line 1	3.795	Quasi-Peak	22.029	10.306	32.335	56.0	-23.665
		3.795	Average	16.375	10.306	26.681	46.0	-19.319
10	Line 1	3.8625	Quasi-Peak	22.515	10.302	32.817	56.0	-23.183
		3.8625	Average	15.107	10.302	25.409	46.0	-20.591

**AC Mains Input, Conducted Test – Line 2: 0.15 MHz to 30.0 MHz**




Top Discrete Measurements								
No.	Conductor	Frequency (MHz)	Detector	Level (dBµV)	Adjustment (dB)	Results (dBµV)	Limit (dBµV)	Margin (dB)
1	Line 2	0.721616	Quasi-Peak	30.005	10.338	40.343	56.0	-15.657
		0.721616	Average	24.639	10.338	34.977	46.0	-11.023
2	Line 2	0.7305	Quasi-Peak	30.371	10.336	40.707	56.0	-15.293
		0.7305	Average	24.650	10.336	34.986	46.0	-11.014
3	Line 2	0.733875	Quasi-Peak	30.523	10.336	40.859	56.0	-15.141
		0.733875	Average	24.715	10.336	35.051	46.0	-10.949
4	Line 2	0.73725	Quasi-Peak	30.429	10.335	40.764	56.0	-15.236
		0.73725	Average	24.220	10.335	34.555	46.0	-11.445
5	Line 2	0.760875	Quasi-Peak	28.903	10.331	39.234	56.0	-16.77
		0.760875	Average	23.468	10.331	33.799	46.0	-12.201
6	Line 2	14.0212	Quasi-Peak	27.846	10.682	38.528	60.0	-21.472
		14.0212	Average	16.622	10.682	27.304	50.0	-22.696

**AC Mains Output, Conducted Test – Line 1: 0.15 MHz to 30.0 MHz**



Top Discrete Measurements								
No.	Conductor	Frequency (MHz)	Detector	Level (dBµV)	Adjustment (dB)	Results (dBµV)	Limit (dBµV)	Margin (dB)
1	Line 1	0.15	Quasi-Peak	55.119	11.555	66.674	80.0	-13.326
		0.15	Average	50.526	11.555	62.081	70.0	-7.919
2	Line 1	0.153375	Quasi-Peak	52.040	11.497	63.537	80.0	-16.463
		0.153375	Average	41.897	11.497	53.394	70.0	-16.606
3	Line 1	0.767625	Quasi-Peak	46.107	10.330	56.437	74.0	-17.563
		0.767625	Average	38.995	10.330	49.325	64.0	-14.675
4	Line 1	0.771	Quasi-Peak	50.028	10.329	60.357	74.0	-13.643
		0.771	Average	45.365	10.329	55.694	64.0	-8.306
5	Line 1	0.7845	Quasi-Peak	49.216	10.327	59.543	74.0	-14.46
		0.7845	Average	41.580	10.327	51.907	64.0	-12.093
6	Line 1	0.787875	Quasi-Peak	50.218	10.326	60.544	74.0	-13.456
		0.787875	Average	46.726	10.326	57.052	64.0	-6.948
7	Line 1	0.798	Quasi-Peak	45.946	10.323	56.269	74.0	-17.731
		0.798	Average	42.401	10.323	52.724	64.0	-11.276
8	Line 1	0.801375	Quasi-Peak	50.454	10.321	60.775	74.0	-13.225
		0.801375	Average	45.019	10.321	55.340	64.0	-8.660
9	Line 1	0.80475	Quasi-Peak	48.244	10.320	58.564	74.0	-15.436
		0.80475	Average	43.848	10.320	54.168	64.0	-9.832
10	Line 1	0.814875	Quasi-Peak	46.324	10.315	56.639	74.0	-17.361
		0.814875	Average	41.522	10.315	51.837	64.0	-12.163

AC Mains Output, Conducted Test – Line 2: 0.15 MHz to 30.0 MHz



Top Discrete Measurements								
No.	Conductor	Frequency (MHz)	Detector	Level (dBµV)	Adjustment (dB)	Results (dBµV)	Limit (dBµV)	Margin (dB)
1	Line 2	0.7575	Quasi-Peak	53.659	10.332	63.991	74.0	-10.009
		0.7575	Average	49.001	10.332	59.333	64.0	-4.667
2	Line 2	0.760875	Quasi-Peak	50.370	10.331	60.701	74.0	-13.299
		0.760875	Average	45.366	10.331	55.697	64.0	-8.303
3	Line 2	0.771	Quasi-Peak	52.685	10.329	63.014	74.0	-10.986
		0.771	Average	47.057	10.329	57.386	64.0	-6.614
4	Line 2	0.774375	Quasi-Peak	53.103	10.328	63.431	74.0	-10.569
		0.774375	Average	48.421	10.328	58.749	64.0	-5.251
5	Line 2	0.77775	Quasi-Peak	47.437	10.328	57.765	74.0	-16.24
		0.77775	Average	41.078	10.328	51.406	64.0	-12.594
6	Line 2	0.7845	Quasi-Peak	50.362	10.327	60.689	74.0	-13.311
		0.7845	Average	46.884	10.327	57.211	64.0	-6.789
7	Line 2	0.787875	Quasi-Peak	54.508	10.326	64.834	74.0	-9.166
		0.787875	Average	50.341	10.326	60.667	64.0	-3.333
8	Line 2	0.79125	Quasi-Peak	51.429	10.325	61.754	74.0	-12.246
		0.79125	Average	46.806	10.325	57.131	64.0	-6.869
9	Line 2	0.801375	Quasi-Peak	52.618	10.321	62.939	74.0	-11.061
		0.801375	Average	49.488	10.321	59.809	64.0	-4.191
10	Line 2	0.80475	Quasi-Peak	53.115	10.320	63.435	74.0	-10.565
		0.80475	Average	47.999	10.320	58.319	64.0	-5.681

**Test Equipment Used:**

Equipment Type	Asset Number	Manufacturer	Model	Serial Number	Calibration Due Date
Temp/Hum. Rec.	CL119	Extech	RH520	H005869	Dec. 28, 2018
Transient Limiter	CL102	Hewlett Packard	11947A	3107A03325	Mar. 8, 2019
Software:	Tile Version 3.4.B.3.		Software Verified: Mar. 22, 2018		
Spectrum Analyzer	CL147	Agilent	E7402A	MY45101241	Nov. 16, 2018
LISN	CL181	Com-Power	LI-125A	191226	June 24, 2018
LISN	CL182	Com-Power	LI-125A	191225	June 24, 2018

**Exhibit IV**

**Photographs**

**Conducted Emissions**

**AC Mains Input**



**AC Mains Output**



## **Exhibit V**

### **Modifications**

No modifications were made to the EUT that contained the design changes outlined in Exhibit II of this Test Report.

## Exhibit VI


### Labeling of Equipment

It will be the responsibility of the manufacturer or importer to permanently affix the appropriate label prior to marketing in Canada for equipment manufactured in Canada; and prior to importation into Canada for imported equipment.

The presence of the label on the equipment represents the manufacturer's or importer's Self-Declaration of Compliance (SDoC) to the appropriate Industry Canada rule. Each unit of an equipment model shall bear a label indicating the model's compliance with that rule.

The label shall be permanently affixed to the equipment or displayed electronically and its text must be clearly legible. When the dimension of the device is too small or it is otherwise not practical to place the label on the equipment, the label shall be placed in a prominent location in the user manual supplied with the equipment. The user manual may be in an electronic format and must be readily available.

The minimum requirements for labeling of models complying with the technical requirements are detailed in Section 8 of ICES-003 Issue 6/ICES-001, Issue 4, as applicable.



*\*Insert either "A" or "B" but not both to identify the applicable Class of ITE/ISM/Digital Device.*

*For example, if the EUT is determined to be Class A, then the minimum label requirement shall be displayed as follows: CAN ICES-3(A)/NMB-3(A) or ICES-1(A)/NMB-1(A), as applicable. If Class B, then the minimum label requirement shall be displayed as follows: CAN ICES-3(B)/NMB-3(B) or ICES-1(B)/NMB-1(B), as applicable.*